

# ECHO SERIES

Single, Duo and Trio





## ECHO SERIES

### In Desk Solutions

CMS Echo series delivers the latest charging technology to empower engaging and connected spaces within the commercial workplace, integrating into personal workstations, soft-seating and collaborative spaces.

Echo is available in 3 shell sizes, Single, Duo and Trio, describing the number of modules each shell can accommodate. Echo can be equipped with any combination of; USB C+A Charging, Wireless Charging and standard Power.

The module has a shallow depth of 46mm, with easy top-side installation without fastening from the bottom.

### Features & Benefits

- » Minimalistic surface design blends into any surface.
- » Surface installation suited to soft seating and custom joinery.
- » Fast-charge options include 30W USB-C PD fast-charging or 15W Wireless fast-charging.
- » Available to be configured with lead with C series plug or BS13A 3-pin plug.
- » Standard colours black and white.
- » Charging services to be used with IT equipment only



### Colours Available

○ White ● Black

## Product Details

### Echo Single

<b>ECBSN01C10**</b>	1 power module, 1000mm lead, C series plug
<b>ECBSN01B15**</b>	1 power module, 1500mm lead with BS13A 3-pin plug
<b>ECUACC10**</b>	USB C/A PD fast charge module (30W shared), 1000mm lead, C series plug
<b>ECUACB15**</b>	USB C/A PD fast-charge module (30W shared), 1500mm lead with BS13A 3-pin plug
<b>ECWCC10**</b>	Wireless fast-charge module (15W), 1000mm lead, C series plug
<b>ECWCB15**</b>	Wireless fast-charge module (15W), 1500mm lead with BS13A 3-pin plug

### Echo Duo

<b>EDC1C1C10**</b>	2 gang power module, 1000mm lead with C series plug
<b>EDC1C1G15**</b>	2 gang power module, 1500mm lead with BS13A 3-pin plug
<b>EDC1UC10**</b>	1 power module, USB C/A PD fast-charge module (30W shared), 1000mm lead with C series plug
<b>EDC1UG15**</b>	1 power module, USB C/A PD fast-charge module (30W shared), 1500mm lead with BS13A 3-pin plug
<b>EDC1WC10**</b>	1 power module, Wireless fast-charge module (15W), 1000mm lead with C series plug
<b>EDC1WG15**</b>	1 power module, Wireless fast-charge module (15W), 1500mm lead with BS13A 3-pin plug
<b>EDUWC10**</b>	USB C/A PD fast-charge module (30W shared), Wireless fast-charge module (15W), 1000mm lead with C series plug
<b>EDUWG15**</b>	USB C/A PD fast-charge module (30W shared), Wireless fast-charge module (15W), 1500mm lead with BS13A 3-pin plug

### Echo Trio

<b>ETC1C1C1C10**</b>	3 gang power module, 1000mm lead with C series plug
<b>ETC1C1C1G15**</b>	3 gang power module, 1500mm lead with BS13A 3-pin plug
<b>ETC1UC1C10**</b>	1 power module, USB C/A PD fast-charge module (30W shared), 1 power module, 1000mm lead with C series plug
<b>ETC1UC1G15**</b>	1 power module, USB C/A PD fast-charge module (30W shared), 1 power module, 1500mm lead with BS13A 3-pin plug
<b>ETC1UWC10**</b>	1 power module, USB C/A PD fast-charge module (30W shared), Wireless fast-charge module (15W) 1000mm Tlead with C series plug
<b>ETC1UWG15**</b>	1 power module, USB C/A PD fast-charge module (30W shared), Wireless fast-charge module (15W) 1500mm lead with BS13A 3-pin plug

# Product Specifications

## Wireless Charger

Input	100-240V; 50/60Hz; 0.5A
Max output total	5V DC/5W; 9V DC/15W; 12V DC/15W
Standby power	0.3W
Operating temperature range	0-40C
Compliance	IEC 60950.1 CISPR32:2015

## USB Charger

Input	100-240V AC; 50/60Hz, 0.8A
USB outlets	1 x Type-C PD3.0 fast charge 1 x Type-A standard fast charge
Standby power	<0.15W
Over voltage protection	20-24V
Overcurrent protection	4.3-5.5A
Short circuit protection	USB will shut down if short circuit detected and will recover once short circuit removed.
Operating temperature range	0-40C
Compliance	AS/NZS 60950.1 CISPR32:2015

### USB-C PD Specification

Max standard output with no connected devices in Port 1	3A@5V; 3A@9V; 2.5A@12V; 2A@15V; 1.5A@20V
Max output with Type-C Port engaged	2A@5V

### USB-A Specification

Max standard output with no connected devices in Port 2	3A@5V; 2A@9V; 1.5A@12V
Max output with Type-A Port engaged	2A@5V