

FREEDOM NEXUS

Portable Power

The Freedom Nexus takes portable power to the next level. From training tables to lounges, the Nexus provides the solutions to suit the demands the modern workplace.

If you're looking for a high-capacity, high-output portable power solution, then look no further than the Freedom Nexus Series.



FR210PBPH - Power Bank

FR210TRLYBK - Nexus Battery Trolley



FR210CS - Charging Station



FR210DS - Docking Station

Nexus Battery & Chargers

FR210PBP**	1x 118W USB-A/C PD Power Bank (Push Button Release)
FR210PBPH**	Nexus Power Bank with Handle - Push Button Release
FR210PBK**	1x 118W USB-A/C PD Power Bank (Key Release)
FR210PBKH**	Nexus Power Bank with Handle - Key Release
FR210DS**	1x Docking Station With Multiple Outputs
FR210CS**	1x Charging Station + 150W Power Supply With 10A 3-Pin Plug

Notes:

- ** Denotes Colour: Black (BK), White (WT)
- For use with IT equipment only

Nexus Battery Trolley

FR210TRLYBK	Freedom Nexus Battery Trolley - Black
-------------	---------------------------------------

Dimensions (Excl. Wheels)	372mm(W) x 812mm(H) x 640mm(D)
---------------------------	--------------------------------

PRODUCT DATA SHEET

Power Bank (FR210PBP)

Capacity	9,540mAh (206wh)	
Charging Output	USB-C Port PD 100W (5V3A,9V3A,12V3A,15V3A,20V5A,) or QC3.0/2.0 18W (5V/3A,9V/2A,12V/1.5A) USB-A Port QC3.0/2.0 18W (5V/3A,9V/2A,12V/1.5A)	
Charging Total	Total 118W (PD100W and QC18W)	
Protection	Over-Charge Over-Discharge Over-Current Over-Temperature Short Circuit	
Charging Input Methods	USB-C Port When Factory Enabled/(Disabled By Default): PD 60W Max (5V,9V,12V,15V,20V) Charging Station Docking Station	
Indicators	4pcs x LEDs White Colour	
Size	L=251.8 W=151.4 H=38.1	
Weight	1054 kg	
Compliance	IEC62133 & IEC62368 UL2056 CE-EMC (EN 55032, EN 55035)	RoHS UN38.3 USB-IF(PD)

Docking Station (FR210PS)

Input	7.4x5.0 DC Jack (To Recharge Units While Docked) 20v/5A	
Output Ports	USB-C output : PD 100W (5V3A,9V3A,12V3A,15V3A,20V5A,) or QC3.0/2.0 18W (5V/3A,9V/2A,12V/1.5A). USB-A output : QC3.0/2.0 18W (5V/3A,9V/2A,12V/1.5A). DC OUT1 (XT60) : 18-25.2V(Battery voltage output directly) ,16-18A. DC OUT2 (XT60) : 12V/18V/20V/24V,11A. Max combined output 150W - 1 docked, 350W - 2+ units docked	
Docking Capability	Up to 3x Nexus Power Banks (630Wh)	
Capacity Indicators	4x White LEDs To Indicate The Battery Level Of The Docked Power Banks.	
Size	L= 275.9 W=152.2 H31.6	
Weight	0.94 kg	
Compliance	RCM (AS/NZS CISPR32) CE-EMC (EN 55032, EN 55035)	

Charging Station (FR210CS)

Input	7.4x5.0 DC jack : 20V7.5A	
Max Power Banks	Up To Max 5x Power Banks.	
LED Indicator	Always On When Power Available.	
Charging Time	Charging Station – 5 Docked (DC Input Power 150W) : 9-10 hours Charging Station – 3 Docked (DC Input Power 150W) : 6-7 hours Charging Station – 1 Docked (DC Input Power 150W) : 2-3 hours	
Size	L= 326.4 W=199.3 H=99	
Weight	1088 kg	
Compliance	RCM (AS/NZD CISPR32) CE-EMS (EN 55032, EN 55035)	

Disclaimer: CMS Electracom has made every attempt to ensure the accuracy and reliability of the information provided in this document are correct. All information contained in this document is to be used for general guidance only. CMS Electracom reserves the right to change, delete or modify the information without notice. V1 2026.
For product warranty and returns see cmselectra.com/au/resources/warranty/
© CMS Electracom 2026

