

# J16 & JSW SERIES

## For power/data/communications



J16.1



J16.2



JSW

### SOME OF THE FEATURES INCLUDE:

- Data available in 1,2 or 3 outlet data configuration
- Compliant with AS/NZS61535.1:2003

### CUT OUT SIZES:

- **J16.1** - Contact staff for template
- **JSW** - Contact staff for template

ORDERING INFORMATION	
PART NO.	DESCRIPTION
J16.1**	Single 10amp GPO with 20amp installation coupler, double pole switched
J16.2**	Double 10amp GPO with 20amp installation coupler, double pole switched
JSW1BG	Single Switch Plate (Extra low voltage only, not for 240volt)
JSW2BG	Double Switch Plate (Extra low voltage only, not for 240volt)
JSW3BG	Triple Switch Plate (Extra low voltage only, not for 240volt)

**PLEASE CALL US FOR THE MOST UP TO DATE SPECIFICATIONS AND PRICING**

#### Notes:

- Standard colours for GPOs are Beige and White (others by request)
- Standard colour for data is beige only
- \*\*Denotes colour: BG (beige), WT (white)

# SW19 - Triple GPO

## For thin panel mounting



SW19P03

### SOME OF THE FEATURES INCLUDE:

- New mini connector built into this GPO
- **SW19P03** Standard module will snap directly into panel cut out up to 2mm thick
- Standard GPO colours are Black or White (others by request)
- 3 x triple auto switched socket outlet
- Compliant with AS/NZS61535.1:2003

### CUT OUT SIZES:

- **SW19P03** - 161mm x 55mm

ORDERING INFORMATION	
PART NO.	DESCRIPTION
SW19P03**	Triple auto switched power module with facia - 10amp
PLEASE CALL US FOR THE MOST UP TO DATE SPECIFICATIONS AND PRICING	

*Notes:*

- Standard colours are Black and White
- \*\*Denotes colour: BG (beige), WT (white)
- Refer to pages 74 & 75 for interconnecting leads

## J SERIES

### Connectors, mounting block & shroud

The mounting block is a spacer between the work surface and the power/  
Data plate to allow for easy installation



#### ORDERING INFORMATION

PART NO.	DESCRIPTION
JMBBG	Mounting block



#### ORDERING INFORMATION

PART NO.	DESCRIPTION
J16CBG	Shroud (back cover - mounts on work surface behind cut out)




#### ORDERING INFORMATION

PART NO.	DESCRIPTION
JTV**	TV Outlet



#### ORDERING INFORMATION

PART NO.	DESCRIPTION
J3D**	1 in 2 out double adaptor



#### ORDERING INFORMATION

PART NO.	DESCRIPTION
J3E**	20amp Triple adaptor, 1 in / 3 out



ORDERING INFORMATION	
PART NO.	DESCRIPTION
I10A**	Switch 10amp, 250volt 2 way with looping terminal (without indicator)



ORDERING INFORMATION	
PART NO.	DESCRIPTION
I10**	Switch 10amp, 250volt with looping terminal, with indicator - (not to be used as a 2 way switch)



ORDERING INFORMATION	
PART NO.	DESCRIPTION
JSW1A**	Switch surface mount



ORDERING INFORMATION	
PART NO.	DESCRIPTION
JOL10**	10amp double pole auto switch socket outlet IP44 to J3.1 installation coupler



ORDERING INFORMATION	
PART NO.	DESCRIPTION
JIL15**	15amp Plug power inlet IP44 to J3.2 installation coupler



ORDERING INFORMATION	
PART NO.	DESCRIPTION
JODCWT	Power outlet



ORDERING INFORMATION	
PART NO.	DESCRIPTION
JOL02	Double 20amp auto switch socket outlet with J3.1 installation coupler

*Notes:*

- Standard colour for shroud & mounting block beige only
- \*\*Denotes colour: BG (beige), WT (white)

# INTERCONNECTING CABLES

## ROHS - white only



ROHS leads are manufactured from 3 core 2.5sqmm flexible cable, are rated at 20Amp, terminated with male plug and female socket 'CMS' AS/NZ61535.1 compliant connectors.

ORDERING INFORMATION	
PART NO.	DESCRIPTION
JL05WT	500mm Interconnecting lead 20amp, 2.5mm - White
JL10WT	1000mm Interconnecting lead 20amp, 2.5mm - White
JL15WT	1500mm Interconnecting lead 20amp, 2.5mm - White
JL20WT	2000mm Interconnecting lead 20amp, 2.5mm - White
JL25WT	2500mm Interconnecting lead 20amp, 2.5mm - White
JL30WT	3000mm Interconnecting lead 20amp, 2.5mm - White
JL35WT	3500mm Interconnecting lead 20amp, 2.5mm - White
JL40WT	4000mm Interconnecting lead 20amp, 2.5mm - White
JL45WT	4500mm Interconnecting lead 20amp, 2.5mm - White
JL50WT	5000mm Interconnecting lead 20amp, 2.5mm - White

**PLEASE CALL US FOR THE MOST UP TO DATE SPECIFICATIONS AND PRICING**

*Notes:*

- Standard colours is white

# INTERCONNECTING CABLES

## ROHS - beige only



ROHS leads are manufactured from 3 core 2.5sqmm flexible cable, are rated at 20Amp, terminated with male plug and female socket 'CMS' AS/NZ61535.1 compliant connectors.

ORDERING INFORMATION	
PART NO.	DESCRIPTION
JL05BG	500mm Interconnecting lead 20amp, 2.5mm - Beige
JL10BG	1000mm Interconnecting lead 20amp, 2.5mm - Beige
JL15BG	1500mm Interconnecting lead 20amp, 2.5mm - Beige
JL20BG	2000mm Interconnecting lead 20amp, 2.5mm - Beige
JL25BG	2500mm Interconnecting lead 20amp, 2.5mm - Beige
JL27BG	2700mm Interconnecting lead 20amp, 2.5mm - Beige
JL30BG	3000mm Interconnecting lead 20amp, 2.5mm - Beige
JL38BG	3800mm Interconnecting lead 20amp, 2.5mm - Beige
JL42BG	4200mm Interconnecting lead 20amp, 2.5mm - Beige
JL47BG	4700mm Interconnecting lead 20amp, 2.5mm - Beige
JL57BG	5700mm Interconnecting lead 20amp, 2.5mm - Beige
JL63BG	6300mm Interconnecting lead 20amp, 2.5mm - Beige
JL68BG	6800mm Interconnecting lead 20amp, 2.5mm - Beige

**PLEASE CALL US FOR THE MOST UP TO DATE SPECIFICATIONS AND PRICING**

*Notes:*

- Standard colours is beige