

# INLINE USB-CC 65W

Qualcomm® & Power Delivery (PD) Intelligent Charging





## INLINE USB-CC 65W

### Qualcomm® & Power Delivery (PD) Intelligent Charging

CMS is consistently developing and updating its power, data and charging modules, adapting products to suit the latest user requirements and applications. The Inline USB-C module features both Qualcomm® Quick Charge™ and PD technology capable of delivering up to 4 x faster charging to Qualcomm® and PD enabled devices.

### Product Details

**SW18UAC65**

SW18 Series Inline USB-C 65W Module with Qualcomm® & PD Intelligent Charging

### Colours Available

White  Black

### Key Features

- Dedicated USB-C port with indicator light to differentiate between standard and Qualcomm® / PD fast-charging.
- Inline USB-C 65W can be integrated to suit above, below and recessed applications in a range of housings.
- Optimised Fast Charging to Apple, Android & Windows Devices.

## Product Specifications

Input	100-250V AC
USB outlets	1 x USB-C - Qualcomm® & PD Intelligent Charging USB-C standard charge USB-C Qualcomm
Standby power	0.3W
Over voltage protection	24V for 20V output
Overcurrent protection	110-130% I <sub>o</sub>
Short circuit protection	USB will shut down if short circuit detected and will recover once short circuit removed
Over power protection	70W
Operating temperature range	0-40C
Compliance	AS/NZS 62368-1 AS/NZSCISPR32 IEC 62368-1 CISPR32:2015

### Port 1: Qualcomm® Quick Charge™ Specification

Quick Charge™ 2.0 Enabled Devices	2A @ 9V DC 1.5A @ 12V DC
Quick Charge™ 3.0 Enabled Devices	3A @ 3.6 - 6.5V DC 2A @ 6.5 - 9.V DC 1.5A @ 9 - 12V DC
Charging indication	Blue LED
No charging	LED off
Qualcomm® Quick Charge™ compatible devices	refer <a href="http://www.qualcomm.com/quickcharge">www.qualcomm.com/quickcharge</a>

### Port 1: PD Specification

Max standard output with no connected devices in Port 2	9V/3A, 15V/3A, 20V/3.25A
Max output with USB-C Port 2 engaged (higher than 500mA)	9V/3A, 12V/3A, 20V/2.25A
Charging indication	Blue LED
No charging	LED off

### Port 2: USB-C

Max standard output with no connected devices in Port 1	2.1A @ 5V DC
Max output when Port 1 output exceeds 1.5A	2.1A @5V DC
Max output when Port 1 output lower than 1.5A	2.1A @ 5V DC
Charging indication	Green LED
No charging	LED off