

# ECHO SERIES

## In-Desk Module





## ECHO SERIES

### In Desk Solutions

Designed to enhance productivity and connectivity in dynamic work environments, the Echo Series is ideal for personal workstations, soft seating areas and collaborative spaces. Available in Single, Duo and Trio configurations, Echo offers a combination of Power Outlets, USB Fast Charging and Wireless Charging.


With a shallow depth of just 46mm, the module is designed for easy top-side installation, requiring no fastening from underneath the desk. This design ensures a sleek, streamlined look while simplifying installation and maintaining a clean, organised workspace.

### Colours Available

White  Black






### Key Features

- » Minimalistic design blends into any surface.
- » Surface installation suited to soft seating and custom joinery.
- » USB Fast-Charging up to 65W and 15W Wireless Charging.
- » Available to be configured with softwiring connector or standard 3-pin plug.
- » Standard colours black and white.
- » Power Modules are shuttered.








## Product Details

### Echo Single

	<b>EC01**</b>	GPO with 500mm TAG Lead
	<b>ECUAC3**</b>	USB A/C Fast-Charge Module ( <b>30W Shared</b> ) with 500mm TAG Lead
	<b>ECUAC65**</b>	USB A/C Fast-Charge Module ( <b>65W Shared</b> ) with 500mm TAG Lead
	<b>ECU5**</b>	USB C/C Fast-Charge Module ( <b>65W</b> ) with 500mm TAG Lead
	<b>ECW4D**</b>	Wireless Fast Charge Module ( <b>15W</b> ) with 500mm Tag Lead






\*Products listed above are available with a 3-Pin Plug as an option.

### Echo Duo

	<b>EDA1A1T10D**</b>	2x GPO with 1000mm TAG Lead
	<b>EDA1UT10D**</b>	1 GPO + USB A/C Fast-Charge Module ( <b>30W Shared</b> ) with 1000mm TAG Lead
	<b>EDA1W4T10D**</b>	1 GPO + Wireless Fast-Charge Module ( <b>15W</b> ) with 1000mm TAG Lead
	<b>EDUW4T10D**</b>	USB A/C Fast-Charge Module ( <b>30W Shared</b> ) + Wireless Fast-Charge Module ( <b>15W</b> ) with 1000mm TAG Lead
	<b>EDU5W4T10D**</b>	USB C/C Fast-Charge Module ( <b>65W Shared</b> ) + Wireless Fast-Charge Module ( <b>15W</b> ) with 1000mm TAG Lead

\*Products listed above are available with a 3-Pin Plug as an option.

## Echo Duo

	<b>ETA1A1A1T10D**</b>	3 GPO with 1000mm TAG Lead
	<b>ETA1UA1T10D**</b>	GPO, USB A/C Fast-Charge Module ( <b>30W Shared</b> ), 1 GPO with 1000mm TAG Lead
	<b>ETA1UW4T10D**</b>	1 GPO, USB A/C Fast-Charge Module ( <b>30W Shared</b> ), Wireless Fast-Charge Module ( <b>15W</b> ) with 1000mm TAG Lead
	<b>ETA1U4W4T10D**</b>	1 GPO, USB A/C Fast-Charge Module ( <b>65W Shared</b> ), Wireless Fast-Charge Module ( <b>15W</b> ) with 1000mm TAG Lead
	<b>ETA1U5WT10D**</b>	1 GPO, USB C/C Fast-Charge Module ( <b>65W Shared</b> ), Wireless Fast-Charge Module ( <b>15W</b> ) with 1000mm TAG Lead

\*Products listed above are available with a 3-Pin Plug as an option.

## Product Specifications

### Wireless Charger

Input	100-240V; 50/60Hz; 0.6A
Max output total	15W
Standby power	0.2W
Operating temperature range	0-40C
Compliance	AS/NZS 61558.2.16:2022 CISPR32:2015

### 30W USB Charger

Input	100-240V AC; 50/60Hz, 0.8A
USB outlet	1 x Type-C PD3.0 fast charge 1 x Type-A standard fast charge
Standby power	<0.15W
Over voltage protection	20-24V
Overcurrent protection	4.3-5.5A
Short circuit protection	USB will shut down if short circuit detected and will recover once short circuit removed.
Operating temperature range	0-40C
Compliance	AS/NZS 62368- CISPR32:2015

### USB-C PD Specification

Max standard output with no connected devices in Port 1	3A@5V; 3A@9V; 2.5A@12V; 2A@15V; 1.5A@20V
Max output with Type-C Port engaged	2A@5V

### USB-A Specification

Max standard output with no connected devices in Port 2	3A@5V; 2A@9V; 1.5A@12V
Max output with Type-A Port engaged	2A@5V

# Product Specifications

## 65W USB A+C Charger

Input	100-240V AC; 50/60Hz, 1.8A
USB outlets	1 x Type-C PD3.0 fast charge
	1 x Type-A standard fast charge
Standby power	<0.15W
Over voltage protection	20-24V
Overcurrent protection	4.3-5.5A
Short circuit protection	USB will shut down if short circuit detected and will recover once short circuit removed.
Operating temperature range	0-40C
Compliance	AS/NZS 61558-
	CISPR32:2016
<b>USB-A &amp; USB-C Port Specification</b>	
Max output with both A & C Ports engaged	2.4@5V, 2A@9V, 3A@12V , 3A@15V
Max standard output with no connected devices in A Port	3A@5V , 3A@9V , 3A@12V , 3A@15V , 3.25A@20V
<b>USB C+C Charger</b>	
Input	100-240V AC; 50/60Hz, 1.8A
USB outlets	1 x Type-C PD3.0 fast charge
	1 x Type-A standard fast charge
Standby power	<0.15W
Over voltage protection	20-24V
Overcurrent protection	4.3-5.5A
Short circuit protection	USB will shut down if short circuit detected and will recover once short circuit removed.
Operating temperature range	0-40C
Compliance	AS/NZS 61558-
	CISPR32:2016
<b>USB-C1 &amp; USB-C2 Port Specification</b>	
Max output with both C Ports engaged	2.4@5V, 2A@9V, 3A@12V , 3A@15V
Max standard output with no connected devices in C1 Port	3A@5V , 3A@9V , 3A@12V , 3A@15V , 3.25A@20V

### Notes:

- \*\* Denotes Standard Colours: Black (BK), White (WT)
- Other configurations are available as custom - lead times apply and price is POA.
- For use with IT equipment only.
- Use of cleaning agents: Please ensure cleaning agents are compatible for use on moulded polycarbonate surfaces. Should any sign of degradation, cracking or discolouration be present or occur, immediately discontinue the use of the cleaning agent.
- Although CMS strives to ensure all our products meet or exceeds wireless charging standards, not all wireless charging enabled phones will charge on our wireless charging units due to reasons outside our control. Technology changes, phone profiles, adding protective covers, battery optimisation settings & position of phone on the charger all impact its ability to charge.
- Our wireless chargers are for **mobile phones only**, other accessories including airpods & watches may not be supported. Wireless Chargers are Compatible with MAGSAFE® products of Apple Inc.
- Our Echo Series USB Fast Charging Module has a built-in feature where it will shut down when not used for a while to save power. To use the USB module again, unplug your USB cable and reinsert it.