


# Interconnecting & Starter Leads

Standard interconnecting cables are manufactured from 3 core 2.5mm<sup>2</sup> flexible cable. They are rated at 20A and are terminated with male and female AS/NZ61535.1 compliant connectors. Where mechanical and EMC segregation from communications cabling is required within furniture and umbilicals, plastic and steel conduit casing with heat-shrunk boots are also available. Leads are Halogen Free.

## TAG Interconnecting Leads



SW52  
TAG interconnecting leads  
Standard



SWF52  
TAG interconnecting leads  
Plastic conduit



SWSE52  
TAG interconnecting leads  
Steel conduit

## 3-pin Starter Leads



SWT5  
3-pin starter leads  
10A 3-pin starter into 20A  
TAG connector



SW552  
3-pin starter leads  
HPM 20A 3-pin starter into 20A  
TAG connector (suit HPM 20A GPO only)

## Colours Available

● Black   ○ White   ● Red

## Product Details

### TAG interconnecting leads - standard

<b>SW5205**</b>	20A interconnecting lead - 500mm
<b>SW5210**</b>	20A interconnecting lead - 1m
<b>SW5215**</b>	20A interconnecting lead - 1.5m
<b>SW5220**</b>	20A interconnecting lead - 2m
<b>SW5225**</b>	20A interconnecting lead - 2.5
<b>SW5230**</b>	20A interconnecting lead - 3m
<b>SW5235**</b>	20A interconnecting lead - 3.5
<b>SW5240**</b>	20A interconnecting lead - 4m
<b>SW5245**</b>	20A interconnecting lead - 4.5m
<b>SW5250**</b>	20A interconnecting lead - 5m
<b>SW5260**</b>	20A interconnecting lead - 6m
<b>SW5270**</b>	20A interconnecting lead - 7m
<b>SW5280**</b>	20A interconnecting lead - 8m
<b>SW5290**</b>	20A interconnecting lead - 9m
<b>SW52100**</b>	20A interconnecting lead - 10m

### TAG interconnecting leads, plastic conduit

<b>SWF5205**</b>	20A interconnecting lead in flex conduit with heat shrunk boots - 500mm
<b>SWF5210**</b>	20A interconnecting lead in flex conduit with heat shrunk boots - 1m
<b>SWF5215**</b>	20A interconnecting lead in flex conduit with heat shrunk boots - 1.5m
<b>SWF5220**</b>	20A interconnecting lead in flex conduit with heat shrunk boots - 2m
<b>SWF5225**</b>	20A interconnecting lead in flex conduit with heat shrunk boots - 2.5m
<b>SWF5230**</b>	20A interconnecting lead in flex conduit with heat shrunk boots - 3m
<b>SWF5235**</b>	20A interconnecting lead in flex conduit with heat shrunk boots - 3.5m
<b>SWF5240**</b>	20A interconnecting lead in flex conduit with heat shrunk boots - 4m
<b>SWF5245**</b>	20A interconnecting lead in flex conduit with heat shrunk boots - 4.5m
<b>SWF5250**</b>	20A interconnecting lead in flex conduit with heat shrunk boots - 5m
<b>SWF5260**</b>	20A interconnecting lead in flex conduit with heat shrunk boots - 6m
<b>SWF5270**</b>	20A interconnecting lead in flex conduit with heat shrunk boots - 7m
<b>SWF5280**</b>	20A interconnecting lead in flex conduit with heat shrunk boots - 8m
<b>SWF5290**</b>	20A interconnecting lead in flex conduit with heat shrunk boots - 9m
<b>SWF52100**</b>	20A interconnecting lead in flex conduit with heat shrunk boots - 10m

\*\*Colour options - black (BK), white (WT) & red (RD)

## Product Details

### TAG interconnecting leads - steel conduit

SWSE5205**	20A interconnecting lead in flex steel conduit with heat shrunk boots - 500mm
SWSE5210**	20A interconnecting lead in flex steel conduit with heat shrunk boots - 1m
SWSE5215**	20A interconnecting lead in flex steel conduit with heat shrunk boots - 1.5m
SWSE5220**	20A interconnecting lead in flex steel conduit with heat shrunk boots - 2m
SWSE5225**	20A interconnecting lead in flex steel conduit with heat shrunk boots - 2.5m
SWSE5230**	20A interconnecting lead in flex steel conduit with heat shrunk boots - 3m
SWSE5235**	20A interconnecting lead in flex steel conduit with heat shrunk boots - 3.5m
SWSE5240**	20A interconnecting lead in flex steel conduit with heat shrunk boots - 4m
SWSE5245**	20A interconnecting lead in flex steel conduit with heat shrunk boots - 4.5m
SWSE5250**	20A interconnecting lead in flex steel conduit with heat shrunk boots - 5m
SWSE5260**	20A interconnecting lead in flex steel conduit with heat shrunk boots - 6m
SWSE5270**	20A interconnecting lead in flex steel conduit with heat shrunk boots - 7m
SWSE5280**	20A interconnecting lead in flex steel conduit with heat shrunk boots - 8m
SWSE5290**	20A interconnecting lead in flex steel conduit with heat shrunk boots - 9m
SWSE52100**	20A interconnecting lead in flex steel conduit with heat shrunk boots - 10m

### 3-pin starter lead with thermal overload

SWT5A10**	20A starter lead - 1m. 10A plug to 20A TAG installation coupler with slimline integrated thermal overload, thermal overload 300mm in from <b>plug</b> .
SWT5A15**	20A starter lead - 1.5m. 10A plug to 20A TAG installation coupler with slimline integrated thermal overload, thermal overload 300mm in from <b>plug</b> .
SWT5A20**	20A starter lead - 2m. 10A plug to 20A TAG Installation coupler with slimline integrated thermal overload, thermal overload 300mm in from <b>plug</b> .
SWT5A25**	20A starter lead - 2.5m. 10A plug to 20A TAG Installation coupler with slimline integrated thermal overload, thermal overload 300mm in from <b>plug</b> .
SWT5A30**	20A starter lead - 3m. 10A plug to 20A TAG installation coupler with slimline integrated thermal overload, thermal overload 300mm in from <b>plug</b> .
SWT5B15**	20A starter lead - 1.5m. 10A plug to 20A TAG installation coupler with slimline integrated thermal overload, thermal overload 300mm in from <b>socket</b> .
SWT5B20**	20A starter lead - 2m. 10A plug to 20A TAG installation coupler with slimline intergrated thermal overload, thermal overload 300mm in from <b>socket</b> .
SWT5B25**	20A starter lead - 2.5m. 10A plug to 20A TAG installation coupler with slimline intergrated thermal overload, thermal overload 300mm in from <b>socket</b> .
SWT5B30**	20A starter lead - 3m. 10A plug to 20A TAG installation coupler with slimline intergrated thermal overload, thermal overload 300mm in from <b>socket</b> .
SWT5L15**	20A starter lead - 1.5m. 10A plug to 20A TAG installation coupler with intergrated thermal overload, <b>with large junction box</b> .
SWT5L30**	20A starter lead - 3m. 10A plug to 20A TAG installation coupler with intergrated thermal overload, <b>with large junction box</b> .

---

HPM 20A starter lead

<b>SW55215**</b>	20A starter lead (HPM 20A plug) - 1.5m
------------------	--

<b>SW55230**</b>	20A starter lead (HPM 20A plug) - 3m
------------------	--------------------------------------

\*\*Colour options - black (BK), white (WT)

**Note:** 20A 3-Pin starter cables are not compatible with standard 10A GPOs.